



CATHODIC UNI-SET INSULATION KIT
Double Washer
Raised Face (Type F)
ASME B 16.5

N.P.S.	150 lb	300 lb	400 lb	600 lb	900 lb	1500 lb	2500 lb
1/2	7.27	7.43	8.24	8.24	10.60	10.60	10.99
3/4	7.27	7.43	8.24	8.24	10.60	10.60	10.99
1	7.27	7.43	8.24	8.24	10.60	10.60	10.99
1 1/4	7.43	7.47	8.53	8.53	10.79	10.79	13.62
1 1/2	7.72	8.43	9.71	9.71	13.26	13.26	15.29
2	7.92	12.05	16.19	16.19	22.46	22.46	27.40
2 1/2	8.47	15.88	18.57	18.57	27.78	27.78	31.32
3	8.77	16.77	19.56	19.56	29.56	30.72	37.08
4	15.60	17.88	24.15	24.15	31.38	36.30	49.52
5	17.30	19.45	26.91	31.41	37.71	50.19	-
6	18.25	28.49	40.04	45.43	52.13	66.24	-
8	20.77	34.32	51.03	52.64	69.01	-	-
10	32.10	52.49	72.74	82.08	94.22	-	-
12	37.68	61.23	85.01	101.11	121.59	-	-
14	45.64	81.05	108.31	112.21	136.69	-	-
16	59.59	89.93	125.28	135.86	-	-	-
18	62.85	109.28	147.77	-	-	-	-
20	76.72	115.59	170.40	-	-	-	-
24	97.74	154.48	-	-	-	-	-